



CRYFISH GLOVES



Description

Passion AL099, CRYFISH GLOVES, are designed with a unique combination of materials for optimal performance. The gloves feature a cotton panel with a full latex coating and latex-laminated palm, providing exceptional grip, waterproofing, and cut resistance.

The poly-cotton ensures comfort and breathability, while the latex coating adds durability and protection. Finished with an embossed texture, these gloves are not only functional but also stylish.

They are perfect for various applications such as finishing, automotive assembly, construction, landscaping, light manufacturing, machine operation, and maintenance work.

Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

Specifications

Style: Crayfish GLOVES
Liner: Cotton
Palm: Latex
Cuff: Composite knit wrist
Mass: ± 110 g per pair (size 10)

Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping.

Store in a cool, dry, dark place. Stored correctly, the gloves physical properties will not change for up to three years.



Cleaning & Maintenance

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands. The gloves may then be decontaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Sizes Available

Code	Size	Palm Length
AL099	10	110mm (± 5 mm)

**As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.*

**Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.*

Measurement Guide



PREFERRED LATEX MATERIAL
Excellent wear resistance, comfortable to wear



COTTON YARN MATERIAL DOUBLE LATEX
Soft lining, comfortable and breathable



ELASTIC CUFF DESIGN
Elastic design is not easy to fall off



129 INDUSTRIAL ROAD AMALGAM JOHANNESBURG SOUTH AFRICA

P.O.BOX 1432 CROWN MINES 2025
www.usafety.co.za