



## SANDY NITRILE COATED ANTI CUTTING GLOVES(LEVEL 5)



### Description

CUT01, cut resistant safety work nitrile sandy gloves.

13 gauge seamless knitted with fibre HPPE, glass fiber, nylon liner, spandex liner. Cut resistance, abrasion resistance, tear resistance and puncture resistance.

Nitrile coating with sandy finish for addition grip, durable and abrasion resistant.

The back is made of nylon material, which is breathable and can absorb sweat, keeping hands dry.

Elastic wrist opening, fit to the hand shape, comfortable to wear, easy to put on and off.

Easy to clean, machine washable, hand washable, non shrinking.

Wide range of uses, glass working, metal material handling, automotive work, electrical wiring, plumbing, general maintenance, industrial warehouse, construction, household gardening, heavy duty work, light industry packaging, textile industry.

### Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

### Compliance & Conformity

EN ISO 21420:2020 General requirements  
5: Dexterity (from 1 to 5)

EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)  
4: Resistance to abrasion (from 1 to 4)  
X: Blade cut resistance  
4: Resistance to tear (from 1 to 4)  
3: Resistance to puncture (1 to 4)  
C: Cut Resistance method (EN ISO 13997) (from A to F)

### Specification:

Style: Sandy nitrile coated ANTI CUTTING gloves  
Liner: Ultra High Molecular Weight Polyethylene(HPPE)  
Palm: Nitrile  
Cuff: Wrist elastic cuff  
Cut level: 5

### Packaging, Storage & Obsolescence

Packed 12 pairs per bundle and 120 pairs per carton for shipping.


Store in a cool, dry, dark place. Stored correctly, the gloves physical properties will not change for up to three years.



240

### Cleaning & Maintenance

Store in a cool, dry place away from frost and light in their original packaging. In case of superficial dirt: Clean with soap and water, wipe with a cloth and hang in a ventilated area to dry naturally away from any direct fire or source of heat, even for items that got wet during use.



We recommend that no bleaching or oxidizing ingredients or any fabric softeners be used.

Recommended washing temperature is between 40°C and 60°C (104~140°F) with mild detergents.

Drying temperature should not exceed 70°C (158°F). There is no remarkable impact on cut resistance during the normal life cycle of a glove, however depending on glove construction, staining and cleaning method the differences in shrinkage and colour may occur. In order to maximize the glove life cycle, we recommend the mildest possible cleaning conditions in terms of temperature, chemicals and cycle duration.

### Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

*\*As per the EN21420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.*

*\*Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.*

### Marking



### Measurement Guide



129 INDUSTRIAL ROAD AMALGAM JOHANNESBURG SOUTH AFRICA  
P.O.BOX 1432 CROWN MINES 2025  
www.usafety.co.za