



## MECHANICAL RED GLOVES



### Description

Passion AB00150, Mechanical Red Gloves, available in sizes M, L, and XL, are designed for maximum comfort and durability in industrial applications. Featuring an anti-shrink synthetic leather, these gloves maintain their shape and fit over time. Equipped with Velcro for easy adjustment, the gloves offer a secure and customizable fit. The addition of towel cloth fabric on the palm provides exceptional grip for "sweet" cleanup tasks. Reinforced saddle sections constructed from synthetic leather offer extra protection in high-wear areas. The gloves feature a soft fabric back for breathability and comfort, paired with a synthetic palm for superior durability. The Velcro cuff ensures a secure closure, preventing debris from entering while maintaining flexibility and ease of use.

### Special Instructions

Although the manufacturer has examined these gloves under the system for ensuring quality of production by means of monitoring and inspection, we recommend that all gloves should be thoroughly inspected before use to ensure no damage is present.

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. The gloves and information contained herein are designed to accommodate the basic safety requirements and standards for Personal Protective Equipment. Actual conditions of use cannot be directly simulated in a test environment, therefore it is the responsibility of the user and not the manufacturer or supplier to determine the suitability for intended use.

### Specifications

Style:	Mechanical gloves
Palm:	Synthetic
Back:	Flex fabric
Cuff:	Velcro cuff

### Packaging, Storage & Obsolescence

Packed 1 pairs per opp bag and 120 pairs per carton for shipping.  
Store in a cool, dry, dark place. Stored correctly, the gloves physical properties will not change for up to three years.



### Cleaning & Maintenance

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands. The gloves may then be decontaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement.

### Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for.  
Please consider recycling.

### Sizes Available

Code	Size	Palm Length
AB00150	10	105mm ( $\pm 2$ mm)

*\*As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.*

*\*Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.*

### Measurement Guide



129 INDUSTRIAL ROAD AMALGAM JOHANNESBURG SOUTH AFRICA

P.O.BOX 1432 CROWN MINES 2025  
[www.usafety.co.za](http://www.usafety.co.za)