



IMPACT RESISTANT GLOVES



Description

Passion IMP03, Impact Resistant Gloves are an industrial-grade solution designed to provide comprehensive protection for hands in demanding work environments. Engineered with TPR, Osman, and ultra-fine fiber, these gloves excel in durability and safety. They feature anti-collision, anti-slip, and abrasion-resistant properties, ensuring stability and safety in oilfields and other hazardous applications. The gloves also offer protection against impacts, heat, and cuts, making them a reliable choice for workers. Furthermore, the Anti-Vibration technology reduces hand fatigue, enhancing comfort and productivity.

Special Instructions

Despite the rigorous quality assurance system implemented by the manufacturer, including monitoring and inspection, we advise that all gloves should undergo a comprehensive check prior to use to certify their integrity and absence of any defects.

The materials and manufacturing processes employed in the creation of these products are not known to pose any harm to the wearer. The gloves and accompanying information are crafted to fulfill the fundamental safety prerequisites and norms for Personal Protective Equipment.

It is important to note that actual usage conditions cannot be precisely replicated in a testing environment. Therefore, it is solely the responsibility of the user, not the manufacturer or supplier, to assess the suitability of the gloves for their intended purpose.

Specifications

Style:	High visibility, reusable, with silicone coated, TPR (Thermo Plastic Rubber) finger and back of hand protection
Palm:	Synthetic with silicone coated, anti slip
Back:	Knuckle region, with TPR (Thermo Plastic Rubber)
Cuff:	Impact protection Neoprene cuff

Packaging, Storage & Obsolescence

Packed 1 pairs per opp bag and 120 pairs per carton for shipping. Store in a cool, dry, dark place. Stored correctly, the gloves physical properties will not change for up to three years.



120

Cleaning & Maintenance

Gloves should not be left in contaminated condition if re-use is intended especially if potential hazards exist. Before removal from the hands excess contaminant should first be removed. Should this not be possible, it is advisable to ease left and right hand gloves off using the gloved hand and remove the gloves without the contaminant contacting the bare hands. The gloves may then be decontaminated with mild detergent solution, then rinsed with clean water and dried ideally with some air movement.

Disposal

All industrial waste should be disposed of correctly according to local regulations and good disposal practice. Gloves should be disposed of considering the hazardous substances they were used for. Please consider recycling.

Sizes Available

Code	Size	Palm Length
IMP03	10	110mm (±2mm)

**As per the EN420 standard, actual measurement of gloves are determined by the manufacturer, taking into account the behaviour of the glove material, its thickness (such as leather gloves, PVC gloves etc), elasticity and the intended use.*

**Sizing charts only serve as a guide. Sizes and measurements are for reference only. In order to make an informed decision, always try on the gloves as each glove features a unique construction to accommodate a wearer's preferences.*

Measurement Guide



USAGE SCENARIO



129 INDUSTRIAL ROAD AMALGAM JOHANNESBURG SOUTH AFRICA

P.O.BOX 1432 CROWN MINES 2025
www.usafety.co.za